



PCT/GB 2003 / 0 0 3 5 1 2

09 FEB 2005



INVESTOR IN PEOPLE

## PRIORITY DOCUMENT

SUBMITTED OR TRANSMITTED IN  
COMPLIANCE WITH RULE 17.1(a) OR (b)

The Patent Office  
Concept House  
Cardiff Road  
Newport  
South Wales  
NP10 8QQ

REC'D 20 OCT 2003

WIPO

PC

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.

Signed

*H. Behen*

Dated

28 August 2003

**BEST AVAILABLE COPY**

13 AUG 2002

NEWPORT

1/77

The Patent Office

Cardiff Road  
Newport  
Gwent NP9 1RH

# Request for grant of a patent

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)

13AUG02 E740573-1 D02776  
P01/7700 0.00 0218776.3

1. Your reference

IP/P3225

2. Patent application number  
(The Patent Office will fill in this part)

0218776.3

13 AUG 2002

3. Full name, address and postcode of the or of each applicant (underline all surnames)

QINETIQ LIMITED

Registered Office 85 Buckingham Gate  
London SW1E 6PD  
United Kingdom

Patents ADP number (if you know it)  
If the applicant is a corporate body, give the country/state of its incorporation

8183857001  
GB

4. Title of the invention

PHORETIC DISPLAY DEVICE

5. Name of your agent (if you have one)

PHILIP DAVIES 'et al'

"Address for service" in the United Kingdom to which all correspondence should be sent (including the postcode)

QINETIQ LIMITED  
IP Formalities  
A4 Bldg  
Cody Technology Park  
Ively Road  
Farnborough  
Hants GU14 0LX United Kingdom

Patents ADP number (if you know it)

8312415001

8183857005

6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (if you know it) the or each application number

Country

Priority application number  
(if you know it)

Date of filing  
(day / month / year)

7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application

Number or earlier application

Date of filing  
(day / month / year)

8. Is a statement of inventorship and of right if to grant of a patent required in support of this request? (Answer 'Yes' if:

- a) any applicant named in part 3 is not an inventor, or
  - b) there is an inventor who is not named as an applicant, or
  - c) any named applicant is a corporate body.
- See note (d))

YES (b)

9. Enter the number of sheets for any of the following items you are filing this form. Do not count copies of the same document

Continuation sheets of this form

Description 42

Claim(s) 7

Abstract 1

Drawing(s) 11 + 11

10. If you are also filing any of the following, state how many against each item.

Priority documents

Translations of priority documents

Statement of inventorship and right to grant of a patent (*Patents Form 7/77*)

3 ✓

Request for preliminary examination and search (*Patents Form 9/77*)

1 ✓

Request for substantive examination (*Patents Form 10/77*)

Any other documents  
(please specify)

11. I / We request the grant of a patent on the basis of this application.

Signature

*PHILIP DAVIES*  
PHILIP DAVIES

Date  
12.8.02

12. Name and daytime telephone number of person to contact in the United Kingdom Linda Bruckshaw 01252 392722

#### Warning

*After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent of the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.*

#### Notes

- If you need help to fill in this form or have any questions, please contact the Patent Office on 0645 500505.*
- Write your answers in capital letters using black ink or you may type them.*
- If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.*
- If you have attached 'Yes' Patents Form 7/77 will need to be filed.*
- Once you have filled in the form you must remember to sign and date it.*
- For details of the fee and ways to pay please contact the Patent Office.*

PHORETIC DISPLAY DEVICE

The present invention relates to phoretic display devices, and in particular to electrophoretic and magnetophoretic display devices which exhibit non-linear electro-optic and magneto-optic transfer characteristics respectively. The present invention  
5 also relates to a method of fabricating an electrophoretic display having non-linear electro-optic transfer characteristics.

Phoretic displays typically comprise a suspension layer containing finely divided  
10 phoretic particles dispersed within a liquid suspension medium. The spatial distribution of the phoretic particles within the suspension layer may be altered by applying a magnetic or electric field to the device. The particles migrate within the device under the influence of the applied field.

15 Conventional electrophoretic displays comprise a suspension layer containing finely divided electrophoretic particles dispersed within a liquid suspension medium. Such electrophoretic displays operate on the principle that the spatial distribution of the electrophoretic particles within the suspension layer may be altered via an electric potential applied to the device. The electric potential is usually applied to the  
20 suspension layer using electrodes deposited on or near the front and rear surfaces respectively of the display. Using this configuration the electrophoretic particles may be encouraged to migrate between the front and rear surfaces of the display in response to the applied electric potential. An accumulation of the electrophoretic particles near the front or rear display surface alters the optical reflective properties of the suspension  
25 layer in that region and in this manner an image may be formed on the display.

A generic advantage of such electrophoretic displays is the ability to produce high contrast images without the use of polarising filters in the construction of the display.

30 The structure and principle of operation of such an electrophoretic display is described in detail in U.S. Pat. No. 3,668,106. The electrophoretic display panel comprises a cell formed by two opposed transparent insulating substrates which have transparent electrodes formed thereon respectively, and an electrophoretic suspension, which consists of fine particles of coloured electrophoretic material suspended in a coloured  
35 suspension medium, in said cell. When a D.C. voltage is applied to the cell, the

particles are moved and deposited on one electrode according to the polarity of the electrophoretic material. The image formed by the accumulation of the electrophoretic material is observed by reflective light.

- 5 The display described in U.S. Pat. No. 3,668,106 exhibits some temporary stability in that the deposited electrophoretic material will stay on the electrode even after removal of the applied electric field. However the long term permanence of such a display is doubtful since the electrophoretic material merely adheres to the electrodes due to weak van der Waals attraction and electrostatic forces.

10

A major limitation associated with conventional electrophoretic displays of the type described in U.S. Pat. No. 3,668,106 is that the electro-optical transfer characteristic of the display precludes matrix multiplexing of cells within the display. Matrix multiplexing typically involves a plurality of electrodes arranged respectively in rows and columns on  
15 opposing internal surfaces within a display. The cells in a matrix multiplexed display are arranged at the positions where the row and column electrodes overlap and each cell is addressed by applying an electric potential via the appropriate row and column electrodes.

- 20 The above mentioned limitation is caused by a characteristic of the conventional electrophoretic cell whereby the change of optical state depends on the product of time and voltage. That is, nearly any small voltage across a cell will cause it to eventually change its optical state. The magnitude of the applied voltage merely affects the time it takes for the optical change of state to occur. Furthermore, the effect of repeated  
25 application of a small electric potential is cumulative and with sufficient cumulative volt-seconds applied a given picture element (pixel) in the display will change its optical state.

- One fundamental requirement of a display cell when connected in a matrix addressing  
30 fashion is to exhibit a definite threshold, that is a highly non-linear electro-optic transfer characteristic. When a voltage below the threshold value is applied to the cell repeatedly, the optical state of the cell must not change. However, when a voltage above the threshold value (for example twice the threshold value) is applied, the cell is required to quickly change its optical state. If this condition is not met, then the display  
35 will show severe crosstalk. That is, elements that are not required to produce a picture

will begin to turn on and elements that are a requisite part of the picture may begin to turn off.

5 Despite the above mentioned limitation of the electrophoretic cell, several methods have been developed for incorporating a threshold effect in the cell. For example, it is possible to connect in series with the electrophoretic cell another device that exhibits a non-linear electrical characteristic, thereby providing a non-linear electro-optic transfer characteristic. Typically, such non-linear devices may include diodes, zener diodes and varistors.

10 Unfortunately, the use of non-linear devices within the display increases the complexity and hence cost of the overall display. The reliability of the display may also be reduced due to the additional components.

15 Alternatively, an active matrix of thin-film transistors may be employed to switch individual cells within a matrix display. In the case of thin-film transistors used for active matrix addressing of displays, the physical size of the transistors imposes a limitation on the arrangement of the pixels in the display and restricts the resolution of the display.

20 An electrophoretic display which inherently exhibits a non-linear electro-optic transfer characteristic is therefore preferred.

An invention aimed at solving this problem is described in U.S. Pat. No. 4,305,807.

25 The display described in U.S. Pat. No. 4,305,807 utilises a liquid crystal material as the suspension medium within the electrophoretic cell. The cell is configured such that the orientation of the liquid crystal molecules within the cell may be altered in response to an applied electric potential. The applied electric potential must however exceed a critical threshold level for the liquid crystal molecules to change their orientation.  
30 Hence, the definite threshold potential required to re-orientate the liquid crystal molecules within the cell enables X-Y matrix selection of cells within the display.

The display operates on the principle that the apparent viscosity of the liquid crystal suspension medium, as experienced by the electrophoretic particles, varies as a function of the orientation of the liquid crystal molecules within the cell.

- 5 Accordingly, the apparent viscosity of the suspension medium may be spatially modulated in sympathy with the re-orientation of the liquid crystal molecules upon the application of an electric potential to the display.

10 When the apparent viscosity of the suspension medium is high, movement of electrophoretic particles in that region of the display is impeded by the orientation of the liquid crystal molecules. The mobility of the particles within the suspension medium is therefore reduced. Conversely, when the apparent viscosity of the suspension medium is low, movement of electrophoretic particles in that region of the display is not  
15 impeded by the orientation of the liquid crystal molecules. In the latter case the mobility of the particles is increased and the particles may move within the suspension medium under the influence of the applied electric potential.

The anisotropic viscosity of the liquid crystal suspension medium provides a mechanism to control the movement of the electrophoretic particles within the display.  
20

Whilst U.S. Pat. No. 4,305,807 enables X-Y matrix selection of cells within the electrophoretic display, the performance of the display may be limited by the configuration adopted. For example, the apparent viscosity of the liquid crystal suspension medium in the display merely hinders the migration of the electrophoretic  
25 particles in the display in the response to the applied electric field, it does not preclude the movement of the electrophoretic particles. Hence, the display may still exhibit a degree of crosstalk.

It is an object of the present invention to ameliorate at least some of the disadvantages  
30 of the above displays and to provide an improved electrophoretic display. It is another object of the invention to provide an electrophoretic display which exhibits a non-linear electro-optic transfer characteristic and which may be addressed using X-Y matrix selection of cells within the device. It is a further object of the present invention to provide a method of fabricating an electrophoretic display having a non-linear electro-  
35 optic transfer characteristic.

According to a first aspect of the present invention, a phoretic cell comprises a liquid crystal cell having a liquid crystal material and a phoretic particle therein, the phoretic particle being moveable from a first preferred position at a first side of the liquid crystal cell to a second side of the liquid crystal cell on application of a field,

- 5 the liquid crystal cell being adapted such that, when the phoretic particle is not located at the first preferred position, there is a defect associated with the first preferred position and the liquid crystal defect energy of the defect is lower when the phoretic particle is located substantially at the first preferred position within the liquid crystal cell
- 10 than when the phoretic particle is not so located,

such that the applied field must exceed a threshold level to move the phoretic particle from the first preferred position to the second side of the liquid crystal cell.

- 15 A defect, sometimes called a disclination, may be thought of as a discontinuity in the orientation of the liquid crystal molecules as described by the liquid crystal director. In the region immediately surrounding the defect the liquid crystal alignment is highly distorted from its lowest energy state, where the director is parallel everywhere. Hence, there is a large amount of elastic energy associated with the defect. For the purposes
- 20 of this patent specification this elastic energy will be known as the defect energy.

- Defects can take different forms depending on the type of distortion of the liquid crystal surrounding them. Typically defects are categorised by how much and in what direction the orientation of the liquid crystal director rotates around a path enclosing the defect.
- 25 In this way positive and negative sign defects can be defined where the director rotates in opposite senses and the degree of rotation governs the magnitude. This value is known as the defect strength and can be positive or negative. Two defects of opposite sign will attract each other and by moving their centres will mutually reduce their elastic energy. This attraction can continue to the point at which the defect centres combine to
- 30 leave a defect with a strength equal to the sum of the strengths of the original two defects; negative and positive strengths then cancel. In the case where two defects are equal and opposite in strength then the defects effectively annihilate each other leaving no residual defect.



The term "associated" has been used in the foregoing to describe the relationship between the defect and the preferred position within the cell arising due to said defect (e.g. the first preferred position). This nomenclature has been used to convey the fact that, in some circumstances it may be impossible for the particle to reach the position of the defect centre since the particle may be hindered by the cell wall. There will still, however, be a position of the particle which minimises the elastic energy of the system.

In some cases, but not exclusively, the above hindrance by the cell wall may be due to the defect being "virtual". A virtual defect is where the defect centre is actually outside the region of the liquid crystal but it still exerts influence on the behaviour of the liquid crystal. This influence is brought about by the alignment of the liquid crystal at the surface into which the virtual defect is hidden. Typically, a virtual defect may occur in cases where the surface anchoring energy is weak or the surface has a non-zero pretilt.

In the interests of clarity, where there is a reference to a defect in this patent specification, said defect may be a virtual defect hidden in a surface or a conventional defect within the liquid crystal material.

Hereinafter, each defect in the system shall be similarly described as associated with the preferred position within the cell arising due to said defect.

In the present invention, the presence of the phoretic particle distorts the alignment of the liquid crystal material in the vicinity thereof and hence the phoretic particle acts as a mobile defect within the system.

When the phoretic particle is in the bulk of the liquid crystal material it is free to move under the influence of the applied field. However, when the particle is in the vicinity of another defect in the liquid crystal material, an interaction occurs between the defects, thereby reducing the liquid crystal defect energy associated with said defects.

The liquid crystal defect energy of the defect associated with the first preferred position is therefore minimised when the defect associated with the phoretic particle and the defect associated with the first preferred position are superposed. Where the geometry

of the system allows, the defects interact to such an extent that they may be said to effectively annihilate. In this situation the term "defect" shall refer to the core where the defect associated with the first preferred position originally arose.

- 5 Therefore, the first preferred position may be that where the defect associated therewith is superposed with the defect associated with the phoretic particle. However, the geometry of the liquid crystal cell and the geometry of the phoretic particle may not allow such superposition. In this case, the position of the phoretic particle in which the liquid crystal defect energy is minimised (which is the first preferred position) will be  
10 located in the vicinity of the defect and will be dictated by the cell geometry.

- The present invention provides the advantage that when the defect associated with the phoretic particle interacts with the defect associated with the first preferred position, the phoretic particle will tend to be attracted to and adhere to the first preferred position.  
15 Furthermore, the applied field must exceed a threshold level in order to move the phoretic particle from the first preferred position to the second side of the liquid crystal cell. This provides a non-linear transfer characteristic for moving the phoretic particle from the first preferred position within the liquid crystal cell to the second side of the liquid crystal cell.

- 20 Preferably the phoretic particle is moveable reversibly from a second preferred position at the second side of the liquid crystal cell to the first preferred position at the first side of the liquid crystal cell on application of a field,

- 25 the liquid crystal cell being adapted such that, when the phoretic particle is not located at the second preferred position, there is a defect associated with the second preferred position and the liquid crystal defect energy of the defect is lower when the phoretic particle is located substantially at the second preferred position within the liquid crystal cell than when the phoretic particle is not so located,

- 30 such that the applied field must exceed a threshold level to move the phoretic particle from the second preferred position to the first preferred position within the liquid crystal cell.

In a similar manner to that discussed above, the liquid crystal defect energy associated with the second preferred position may therefore be minimised when the defect associated with the phoretic particle and the defect associated with the second preferred position are superposed. Where the geometry of the system allows, the defects interact to such an extent that they may be said to effectively annihilate. In this situation the term "defect" shall refer to the core where the defect associated with the second preferred position originally arose.

By reversing the polarity of the applied field, the phoretic particle is transferable from the first preferred position to the second preferred position and vice versa.

This embodiment of the present invention provides the advantage that when the defect associated with the phoretic particle interacts with the defect associated with the second preferred position, the phoretic particle will tend to be attracted to and adhere to the second preferred position. Accordingly, in this embodiment of the present invention the phoretic particle is moveable between two stable positions, namely at the first and second preferred positions respectively within the liquid crystal cell.

Furthermore, the applied field must exceed a threshold level in order to move the phoretic particle from the second preferred position to the first preferred position within the liquid crystal cell. This provides a non-linear transfer characteristic for moving the phoretic particle from the second preferred position within the liquid crystal cell to the first preferred position within the liquid crystal cell. This configuration also provides the advantage that the phoretic particle is moveable reversibly between the first and second preferred positions within the liquid crystal cell by reversing the polarity of the applied field.

Advantageously the magnitude of the threshold level associated with moving the phoretic particle from the first preferred position to the second preferred position within the liquid crystal cell is different to that for moving the phoretic particle from the second preferred position to the first preferred position within the liquid crystal cell.

The above mentioned difference in the magnitude of the threshold levels results in asymmetric switching thresholds depending on the polarity of the field applied across the liquid crystal cell. Where there is a requirement to control a plurality of such

phoretic cells, for example in a multi-cellular display, such asymmetry facilitates multiplexed matrix addressing and allows a technique known as line ahead blanking to be used to address the cells.

- 5 In a preferred embodiment, the phoretic cell has a plurality of first preferred positions at the first side of the liquid crystal cell, each first preferred position having a defect associated therewith, and a plurality of phoretic particles dispersed within the liquid crystal material. The phoretic cell may have a plurality of second preferred positions at the second side of the liquid crystal cell, each second preferred position having a defect associated therewith. At least one internal surface of the liquid crystal cell may be profiled so as to induce said defects.
- 10

When configured as described above, each phoretic particle within the phoretic cell is moveable between the first and second preferred positions associated therewith and in this manner the cell may be spatially modulated. The above phoretic cell may therefore be used as a multi-cellular phoretic display.

15

- This embodiment of the present invention is beneficial in that the defects are induced in a controllable manner by profiling at least one internal surface of the liquid crystal cell.
- 20 A surface alignment treatment may also be applied to the at least one internal surface of the liquid crystal cell in order to provide a preferred orientation of the liquid crystal material. For example, a surface alignment treatment giving essentially non homeotropic anchoring conditions may be used. A suitable surface treatment is one in which a tangential component of the liquid crystal director is encouraged, providing a tilted or planar alignment. A surface alignment treatment may also be applied to the phoretic particles within the liquid crystal cell. Again, a surface alignment treatment giving essentially non homeotropic anchoring conditions may be used on the phoretic particles.
- 25

- 30 Preferably, the profile comprises an array of indentations each having a depth,  $d$ , the indentations being arranged at a pitch,  $p$ , within the array.

Preferably, the indentations may comprise substantially hemispherical indentations.

Even more preferably the ratio of the depth of the indentations,  $d$ , to the pitch of the indentations,  $p$ , is at least a quarter.

Where the phoretic cell contains a single phoretic particle, the liquid crystal cell may  
5 comprise a liquid crystal droplet. Advantageously, the phoretic cell comprises a plurality of liquid crystal cells, each liquid crystal cell comprising a liquid crystal droplet.

The arrangement of the liquid crystal cell in the form of a liquid crystal droplet or a plurality of liquid crystal droplets facilitates production of said liquid crystal cells.

10

The liquid crystal droplets may be substantially spherical, each liquid crystal droplet having a length,  $L$ , equal to the droplet diameter  $D$ .

Conveniently, the liquid crystal droplets are substantially prolate spheroids, each liquid  
15 crystal droplet having a length,  $L$ , measured along the major axis and a diameter,  $D$ , measured along the minor axis of the liquid crystal droplet, and the first and second preferred positions are arranged substantially in opposition along the major axis of each liquid crystal droplet.

20 In a preferred embodiment, the length,  $L$ , of the liquid crystal droplet is in the range 1-30  $\mu\text{m}$ .

Preferably the length,  $L$ , of the liquid crystal droplet is in the range 5-20  $\mu\text{m}$ .

25 Even more preferably the length,  $L$ , of the liquid crystal droplet is in the range 10-15  $\mu\text{m}$ .

In a preferred embodiment, the diameter of the phoretic particle is in the range 0.2 to 0.8 times that of the liquid crystal droplet.

30

Preferably, the diameter of the phoretic particle is in the range 0.3 to 0.7 times that of the liquid crystal droplet.

Even more preferably, the diameter of the phoretic particle is in the range 0.4 to 0.6  
35 times that of the liquid crystal droplet.

Advantageously, the or each liquid crystal cell further includes an oil soluble dye. The dye may comprise at least one of a dichroic dye, an azo dye, an anthraquinone dye, a pharmaceutical dye, a cosmetic dye, 1-hydroxy-4-[(4-methylphenyl)amino]-9,10-anthracenedione, 2-(2-quinolyl)-1,3-indandione, 1,4-bis[(4-methylphenyl)amino]-9,10-anthracenedione, and 1-[[4-(phenylazo)phenyl]azo]-2 naphthalenol.

In a preferred embodiment, the or each phoretic particle is adapted to reflect electromagnetic radiation incident thereon.

10

Conveniently, the or each phoretic particle comprises titanium dioxide ( $\text{TiO}_2$ ).

Advantageously, the or each phoretic particle has a reflective coating comprising at least one of a metallic coating and a dielectric coating.

15

In another preferred embodiment the or each phoretic particle comprises a composite particle having a plurality of scattering particles adapted to scatter electromagnetic radiation incident thereon dispersed within a carrier. The carrier may comprise a polymer, for example polymethylmethacrylate (PMMA). The scattering particles may

20 comprise titanium dioxide ( $\text{TiO}_2$ ). Alternatively, or in addition, the scattering particles may comprise polymer spheres, each polymer sphere incorporating at least one of a gas cavity and crushed diamond.

The composite phoretic particle maximises scattering of light thereby providing good reflectance. This is a particularly desirable property when the phoretic cell is used in a display device.

25

Preferably, the liquid crystal material is a Nematic liquid crystal material, for example Merck® E7.

30

The applied field may be at least one of an electric field and a magnetic field.

According to a second aspect of the present invention, there is now proposed a display having a first display surface for displaying an image, comprising a phoretic cell

35 according to the first aspect of the present invention,

wherein the phoretic cell is arranged within the display such that the or each first preferred position within the liquid crystal cell is located substantially at the first display surface,

5

the display being operable by the application of a field across the display.

This arrangement of the phoretic cell within the display provides the advantage that the or each phoretic particle reflects light incident on the first display surface when located at the or each first preferred position within the liquid crystal cell.

10

The phoretic cell contained within the display operates in the same manner as in the first aspect of the present invention. In use, the field applied to the display must exceed a threshold level in order to move the phoretic particle from the first preferred position to the second side of the liquid crystal cell or to the second preferred position within the liquid crystal cell. This provides a non-linear transfer characteristic for moving the phoretic particle from the first preferred position within the liquid crystal cell to the second side of the liquid crystal cell / second preferred position within the liquid crystal cell.

15

20

In a preferred embodiment, the display has a second display surface disposed remotely to the first display surface, and comprises at least one phoretic cell having a second preferred position at the second side of the liquid crystal cell,

25 wherein the phoretic cell is arranged within the display such that the or each second preferred position within the liquid crystal cell is located substantially at the second display surface, and

the first and second preferred positions are such that the or each phoretic particle is visible at a display surface when located at one preferred position and is not visible at said display surface when located at the other preferred position.

30

This configuration of the phoretic cell within the display provides the advantage that the or each phoretic particle reflects light incident on a particular display surface when located at one preferred position but does not reflect light incident on that particular

35

display surface when located at the other preferred position. Accordingly, the phoretic particle or particles may be made visible at a given display surface or alternatively the particle or particles may be arranged so that the or each particle is not visible at said display surface.

5

As above, the phoretic cell contained within the display operates in the same manner as in the first aspect of the present invention. In use, the field applied to the display must exceed a threshold level in order to move the phoretic particle from the second preferred position to the first preferred position within the liquid crystal cell. This provides a non-linear transfer characteristic for moving the phoretic particle from the second preferred position within the liquid crystal cell to the first preferred position within the liquid crystal cell.

10

In another preferred embodiment, the display comprises a phoretic cell having a plurality of liquid crystal cells, each liquid crystal cell comprising a liquid crystal droplet, wherein the liquid crystal droplets are disposed within an encapsulant.

15

In this embodiment of the present invention, the display may comprise a micro-encapsulated display. For example, the display may comprise a polymer dispersed liquid crystal display.

20

The encapsulant may comprise at least one of a thermally curable polymer, a polymer curable by electromagnetic radiation and a silicone elastomer. For example, the encapsulant may comprise Dow Corning® Sylgard® 182.

25

Advantageously, the display comprises a phoretic cell having a plurality of liquid crystal droplets, wherein the liquid crystal droplets are substantially prolate spheroids and are arranged such that the major axis of the droplets is substantially orthogonal to a plane parallel with the first display surface.

30

Preferably the display further comprising means for applying at least one of an electric field and a magnetic field across the display. For example, the means for applying the field may comprise an electrode.



Preferably, the display comprises a plurality of electrodes arranged in rows adjacent the first display surface and in columns adjacent the second display surface, the intersection of each row and column electrode defining a pixel within the display, so as to enable matrix addressing of the pixels within the display.

5

The or each electrode may comprise at least one of a metal, Indium Tin Oxide (ITO), and a conductive polymer.

According to a third aspect of the present invention a method of fabricating a display  
10 according to the second aspect of the present invention comprises the steps of

(i) dispersing a plurality of liquid crystal cells, each liquid crystal cell comprising a liquid crystal droplet as described above, into a curable encapsulant,

15 (ii) aligning the liquid crystal cells into a preferred alignment,

(iii) curing the encapsulant to retain the liquid crystal cells therein.

Advantageously, the method further comprises the step of applying the dispersion of  
20 liquid crystal cells and curable encapsulant onto a substrate.

Preferably, the step of aligning the liquid crystal cells into a preferred alignment is performed after the encapsulant has been cured and comprises the step of expanding the cured encapsulant in a direction substantially perpendicular to the substrate,  
25 thereby elongating the liquid crystal cells dispersed therein in a direction substantially perpendicular to the substrate. The step of expanding the cured encapsulant may comprise introducing a material into the cured encapsulant so as to cause the cured encapsulant to swell. The expansion of the encapsulant forces each of the liquid crystal cells to adopt a substantially prolate spheroid configuration. Additionally, the major axis  
30 of the cells is arranged to be substantially orthogonal to a plane parallel with the substrate.

Alternatively, the method comprises the intermediate steps of reversibly deforming the substrate in the plane of the substrate prior to curing the encapsulant and subsequently  
35 returning the substrate to its undeformed state after curing the encapsulant, so as to

perform the step of aligning the liquid crystal cells, such that the cured encapsulant and the liquid crystal cells dispersed therein are compressed in a plane parallel with that of the substrate.

- 5 Compressing the liquid crystal cells in a plane parallel with that of the substrate causes each of the cells to adopt a substantially prolate spheroid configuration. Additionally, the major axis of the cells is arranged to be substantially orthogonal to a plane parallel with the substrate.
- 10 Conveniently, the step of reversibly deforming the substrate comprises at least one of heating and stretching the substrate.

The invention will now be described, by example only, with reference to the accompanying drawings in which;

Figure 1 shows a schematic cross sectional representation of conventional electrophoretic display common in the prior art,

Figure 2 shows a schematic representation of a conventional electrophoretic display for displaying alpha-numeric characters,

Figure 3 shows a schematic cross sectional representation of an electrophoretic display according to the present invention. The means for applying the electric potential to the display have been omitted from the figure for clarity.

Figure 4 shows a schematic cross sectional representation of a bistable electrophoretic display according to the present invention. The means for applying the electric potential to the display have been omitted from the figure for clarity.

Figure 5 shows a cross sectional schematic representation of a micro-encapsulated electrophoretic display according to the present invention. A single micro-encapsulated droplet within the display is shown for clarity. The liquid crystal director alignment in the micro-encapsulated droplet and on particle of electrophoretic material is illustrated.

Figure 6 shows a cross sectional schematic representation of a micro-encapsulated electrophoretic display during operation. A single micro-encapsulated droplet within the display is shown in each of figures 6a-6d for clarity.

Figure 7 shows a cross sectional schematic representation of a composite electrophoretic particle.

Figure 8 show a process for preparing particles of electrophoretic material for incorporation into a micro-encapsulated electrophoretic display. Figure 8a is a flowchart illustrating a process for imparting hydrophobic properties to the particles of electrophoretic material. Figure 8b is a flowchart illustrating a process for fabricating a composite electrophoretic particle incorporating the hydrophobic particles produced by the process of figure 8a.

Figure 9 shows a flowchart illustrating a process for preparing capsules containing liquid crystal (having an electrophoretic particle dispersed therein) for use in a micro-encapsulated electrophoretic display.

5

Figure 10 shows a flowchart illustrating an alternative process for preparing capsules containing liquid crystal (having an electrophoretic particle dispersed therein) for use in a micro-encapsulated electrophoretic display.

- 10 Figure 11 shows a flowchart illustrating a process for fabricating a micro-encapsulated electrophoretic display incorporating the capsules produced by the process of figure 10.

- 15 Figure 12 shows a cross sectional schematic representation of a portion of a micro-encapsulated electrophoretic display according to the present invention.

Referring to Figure 1, a conventional electrophoretic display (1) comprises a cell (2) formed by two opposed transparent insulating substrates (3a,3b) which have transparent electrodes (4a,4b) formed respectively thereon, and an electrophoretic suspension layer (5), which consists of fine particles of electrophoretic material (6) suspended in a suspension medium (7), in the cell. Typically, the particles of electrophoretic material (6) are arranged to be a contrasting colour to that of the suspension medium (7). When an electric potential (8) is applied to the cell (2), the electrophoretic particles (6) are moved and deposited on one electrode (4a,4b) according to the polarity of the electrophoretic material (6), and the thus formed image (9) is observed by reflective light (10). The thickness of the suspension layer (5) can be anywhere from a few micrometres ( $\mu\text{m}$ ) to several tens of micrometres ( $\mu\text{m}$ ) and the display is usually operated by a D.C. voltage.

In practice the transparent insulating substrates (3a,3b) within the cell may consist of two glass plates separated by a spacing of around  $20\mu\text{m}$  and sealed around the edges. The electrodes (4a,4b) on the inside of the glass plates may be formed by means of transparent indium tin oxide (ITO) layers.

If the electrophoretic particles (6) are micrometre-sized and have a density comparable to the density of the liquid suspension medium (7), they will remain in suspension for extended periods of time without settling out. In the above display application, the liquid suspension medium (7) may be dyed some dark colour, e.g. black. Typically, the electrophoretic particles (6) will be a contrasting colour to the that of the liquid suspension medium (7). For example, titanium dioxide may be used for the electrophoretic material due to its high scattering power, giving good reflectance.

In the unenergised state, the cell appears black, i.e., the colour of the liquid suspension medium (7). When an electric potential (8) is applied to the opposing electrodes (4a,4b), the electrophoretic particles (6) migrate to one substrate wall (3a,3b) and cause the appearance of that substrate wall (3a,3b) to change to white. If the electric potential (8) is now removed, the particles continue to stay on the substrate wall (3a,3b) due to weak van der Waals attraction and electrostatic forces. A reversal of the polarity of applied electric potential (8) causes the electrophoretic particles (6) to leave the substrate wall (3a,3b) and travel to the opposite substrate wall.

Referring to Figure 2, if the electrode (4a,4b) on one substrate wall (3a,3b) is in the shape of a character (11), then that character (11) can be made to appear alternately with the above sequence of electric potentials (8) applied. Simple displays having several alpha-numeric characters (11) per display have been fabricated for laboratory demonstrations. In each case every segment (12) of every character (11) is driven individually by a separate driver circuit (13) or driver circuits.

The electro-optical transfer characteristic of such a display (1) normally does not make possible matrix multiplexing of cells. This is caused by a characteristic of the electrophoretic cell (2) whereby the change of optical state is dependent on the product of time and voltage. That is, nearly any small voltage across a cell will cause it to eventually change its optical state.

Referring to Figure 3, an embodiment of an electrophoretic display according to the present invention comprises an electrophoretic system in which particles of an electrophoretic material (6) are suspended in a suspension medium (7) comprising a liquid crystal material (20) and where the geometry of the system is arranged to promote defects (21) within the liquid crystal material (20). A defect (21) may be thought of as a local break in the orientational symmetry of the liquid crystal material (20), for example a local break in the orientational order of the liquid crystal director. Such defects (21) are sometimes referred to as disclinations in the liquid crystal material (20).

In this configuration, the presence of the particles of electrophoretic material (6) distorts the alignment of the liquid crystal material (20) in the vicinity of the particles (6) and hence the particles (6) act as mobile defects (21), or collections of defects, within the system. When the particles of electrophoretic material are in the bulk of the suspension medium (7) they are free to move under the influence of an applied electric potential. However, when a particle is in the vicinity of a defect (21) in the liquid crystal material (20), an interaction occurs between the defects (21), thereby reducing the total liquid crystal defect energy within the system: The total liquid crystal defect energy within the system is minimised when the particle (6) and the defect (21) are as close as possible and in some cases superposed, in which case the defects or disclinations effectively annihilate. When the defects (21) interact or annihilate, the particle (6) will tend to

adhere to the point in the display where the defect (21) originally occurs or occurred (hereinafter referred to as the defect core).

5 In the absence of an applied electric potential, the particle of electrophoretic material (6) will tend to remain at a preferred position associated with the defect core. This is because the energy of the material is lower in this configuration (with the particle (6) close to or on top of the defect core) than when the particle (6) is in the bulk liquid crystal material (20). This provides the advantage that the long term permanence of the image displayed by the device is improved over a conventional electrophoretic display  
10 where the electrophoretic material merely adheres to the surfaces of the display due to weak van der Waals attraction and electrostatic forces.

15 In order to dislodge the particle of electrophoretic material (6) from the preferred position associated with the defect core, an electric potential must be applied to the display which is sufficient to overcome the potential energy barrier associated with separating the defects (21), i.e. in the case where the defects have been annihilated the applied electric potential must be capable of reforming a defect (21) at the defect core and at the particle of electrophoretic material (6).

20 In order to dislodge the particle of electrophoretic material (6) from the preferred position associated with a defect core, an electric potential must be applied to the display that is sufficient to overcome the potential energy barrier associated with separating the defects. As discussed above, defects interact with each other in order to reduce the elastic energy of the liquid crystal. Accordingly the defects associated with a  
25 particle (6) are influenced by the defects associated with the preferred positions in the liquid crystal cell. Typically, in any particular region of the liquid crystal cell one particular defect will dominate. In this way the elastic energy of the system is reduced by moving the particle (6) towards a defect with opposite strength to the defect(s) associated with the particle (6). Conversely work must be done by an applied electric  
30 potential to separate the particle (6) from a defect to which it is attracted. With sufficient work done by the applied electric potential then the particle (6) may be moved to a region of the liquid crystal cell where there is negligible influence on particle from the defect associated with the preferred position in the liquid crystal cell. If insufficient field is applied then the particle will relax back to its initial position. This threshold behaviour

imparts a non-linear electro-optic transfer characteristic to the display and is what makes passive matrix addressing of the device possible.

5 In the interests of clarity, it should be noted that the present invention does not alter the apparent viscosity of the liquid crystal material (20) within the suspension medium (7) to any appreciable extent to provide a non-linear electro-optic transfer characteristic (contrast with U.S. 4,305,807 discussed earlier). Indeed, in the present invention the liquid crystal director is aligned such that the liquid crystal material (20) in the suspension medium (7) always exhibits its lowest viscosity. Moreover, application of an  
10 electric potential to an electrophoretic cell according to the present invention will have negligible effect in terms of changing the alignment of the liquid crystal director. Similarly, the defects (21) or disclinations in the present electrophoretic cell remain unaffected by an applied electric potential since they are created by the geometry of the system and are therefore effectively pinned within the electrophoretic cell.

15 Referring now to Figure 4, a bistable display may be created by arranging defects (21) in the liquid crystal material (20) on opposing surfaces within the electrophoretic display. For example, a first set of defects (21) is arranged on the first (front) surface (24) of the display whilst a second set of defects (21) is arranged on the second (rear)  
20 surface (26) of the display. In this embodiment, the particles of electrophoretic material (6) may be encouraged to migrate from the first surface (24) to the second surface (26) of the display (and vice versa) by the application of an electric potential which exceeds the threshold level.

25 In common with Figure 3, work must be done by the applied electric potential to separate the particle (6) from a defect to which it is attracted. With sufficient work done by the applied electric potential then the particle (6) may be moved to a region of the liquid crystal cell where another defect is dominant. The particle (6) will then relax to a new position in the cell being the preferred position associated with this new defect.  
30 Once the region of greatest influence of this second defect is reached it is no longer required that an electric potential is applied to the cell. In this way a threshold in the applied electric potential is required to move the particle (6) far enough away from its initial position so that it relaxes to a new position in the cell. As before, if insufficient field is applied then the particle (6) will relax back to its initial position.



The bistable display provides the advantage that the particles of electrophoretic material (6) remain bound at the defect cores when no potential is applied the device. Moreover, the particles of electrophoretic material (6) remain substantially bound to the defect cores even in the presence of low level electric potentials (below the threshold level of the device). This is advantageous since such electric potentials are inherent in multiplexed addressing schemes. Image quality and therefore large area addressing capability is therefore ensured by reducing unwanted migration of particles of electrophoretic material (6) within the device.

- 10 The defects (21) or disclinations in the liquid crystal material (20) may be introduced by any conventional geometry that promotes such defects. For example, it is known in the art that the liquid crystal director can be encouraged to adopt a preferred alignment (planar or homeotropic) with respect to the internal surfaces of a conventional liquid crystal display and that periodic features may be applied to these internal surfaces to  
15 introduce disclinations.

In the embodiments of the electrophoretic display illustrated in Figures 3 and 4, the defects (21) in the liquid crystal material (20) are introduced by means of a deep two-dimensional array. Typically, the geometry may comprise an array of indentations, each indentation having a depth d, arranged at a pitch p, within the array. The  
20 indentations need to be sufficiently deep to produce defects (21) in the liquid crystal material and to this end the ratio of the depth of the indentation, d, to the pitch, p, will typically be at least  $\frac{1}{4}$ . In general, deep indentations encourage the formation of defects in the liquid crystal material.

25

$$\frac{\text{Depth of indentation (d)}}{\text{Pitch of indentations (p)}} \geq \frac{1}{4} \quad [1]$$

By way of example, the geometry employed in the electrophoretic display may  
30 comprise substantially hemispherical indentations arranged in a two-dimensional array. The geometry employed in the display may be provided by any conventional method, for example photolithography, embossing etc.

The internal surfaces of the electrophoretic display may require a surface alignment  
35 treatment in order to provide a preferred orientation of the liquid crystal material (20)

within the display. In the embodiments of the electrophoretic display illustrated in Figures 3 and 4, a planar alignment of the liquid crystal material (20) is utilised. A surface alignment treatment may also be required on the particles of electrophoretic material (6) within the display.

5 The strength of the defects (21) in the liquid crystal material (20) and the corresponding magnitude of the potential energy barrier depends on the profile of the geometry used to promote the defects (21) in the liquid crystal material (20). Accordingly, the potential energy barrier and hence the threshold which must be overcome to dislodge the  
10 particles of electrophoretic material (6) from the defect cores may be tailored by varying the profile of the geometry in the display.

Mindful of the addressing requirements of the display, the threshold which must be overcome to dislodge particles of electrophoretic material (6) from the first surface (24)  
15 of the display may be arranged to be different to threshold which must be overcome to dislodge particles of electrophoretic material (6) from the second surface (26) of the display. Consequently, a degree of asymmetry may be incorporated in the electric potential required to move the particles of the electrophoretic material (6) between the first and second surfaces (24,26) of the display, resulting in asymmetric switching  
20 thresholds for positive and negative polarity electric potentials. Where the display comprises a plurality of cells or pixels (multi-cellular display), such asymmetry facilitates multiplexed matrix addressing and allows a technique known as line-ahead blanking to be used to address the display. Line-ahead blanking enables the display to be addressed in a single time slot (i.e. the display may be addressed in half the time it  
25 would otherwise take if line-ahead blanking were not used).

For an example of standard multiplexing schemes known in the art see "The 'Joers/Alvey' Ferroelectric Multiplexing Scheme", PWH Surguy et al.; Ferroelectrics, Volume 122, pp63-79, 1991.

30 Referring to Figure 5, a further embodiment of an electrophoretic display according to the present invention comprises a micro-encapsulated electrophoretic system. The micro-encapsulated electrophoretic system typically comprises an array of droplets (30) containing liquid crystal material (20). Each droplet (30) encloses a particle of  
35 electrophoretic material (6).

As with the foregoing embodiments, the particles of an electrophoretic material (6) are suspended in a suspension medium (7) comprising a liquid crystal material (20). However, in this embodiment, the suspension medium (7) comprises a plurality of  
5 discrete droplets (30) of liquid crystal material (20) arranged within an encapsulant (35), each droplet (30) having an electrophoretic particle disposed therein (6).

For example, the encapsulant (35) may comprise any suitable binder and the micro-encapsulated electrophoretic display is formed by dispersing droplets (30) of liquid  
10 crystal material into the binder.

In a specific example, the micro-encapsulated electrophoretic system may comprise a polymer dispersed liquid crystal (PDLC) display having droplets (30) of liquid crystal material (20) dispersed within a polymer matrix.

15

Referring to Figure 5, the position of the electrophoretic particle (6) within the droplet (30) of liquid crystal material (20) is controlled by careful selection of the liquid crystal anchoring conditions at the interface between the liquid crystal (20) and the internal droplet (30) surface, and the interface between the liquid crystal (20) and the surface of  
20 the electrophoretic particle (6). With essentially non homeotropic anchoring conditions on both the internal surface of the droplet (30) and the surface of the electrophoretic particle (6), the topology shown forces the creation of defects at these surfaces.

A surface alignment treatment may be used to create favourable anchoring conditions  
25 (and hence a favourable alignment of the liquid crystal director) within each droplet (30). A suitable surface treatment is one in which a tangential component of the liquid crystal director is encouraged, providing a tilted or planar alignment.

The surface alignment treatment encourages the formation of a first (31) and a second  
30 (32) defect within the droplet. The positioning of the defects (31,32) within each droplet (30) is governed by the droplet geometry. Accordingly, the geometry of the droplet (30) may be customised to control the position of the defects (31,32) within the droplet and to ensure that the defects (31,32) are arranged substantially in opposition within the droplet. For example, the droplet (30) may be arranged to be a sphere or a spheroid  
35 (rather than perfectly spherical). In particular, the droplet (30) may be customised to

exhibit a prolate spheroid configuration with the defects (31,32) arranged substantially in opposition along the major (long) axis of the prolate droplet (30).

5 The creation of two defects (31,32) within each droplet (30) provides two possible positions for the particle of electrophoretic material (6) to adopt and hence facilitates a display with image memory.

10 A surface alignment treatment may be applied to the particle of electrophoretic material (6) suspended within each droplet (30). The surface treatment applied to the particle of electrophoretic material (6) should encourage a tangential component of the liquid crystal director, again providing a tilted or planar alignment on the surface of the particle (6). The surface alignment treatment is used to promote two opposing defects (33, 34) on the surface of the particle of electrophoretic material (6).

15 As shown in Figure 5, when the electrophoretic particle (6) is disposed within the bulk of the liquid crystal material (20) i.e. away from the defects (31,32) within the droplet (30), then the system will exhibit a certain liquid crystal defect energy due to the defects (31,32) within the droplet (30) and the defects (33,34) on the surface of the particle (6). The total defect energy within the system is a function of the strength and  
20 location of the defects (31,32,33,34) within in the system.

The particle of electrophoretic material (6) may be encouraged to migrate within the droplet (30) by the application of an electric potential to the droplet (30).

25 When a defect (33,34) on the surface of the particle (6) is in the vicinity of a defect (31,32) within the droplet (30), an interaction occurs between the defects. When the particle (6) is in the vicinity of a defect (31,32) within the droplet (30), the total liquid crystal defect energy within the system is lower than when the electrophoretic particle (6) is disposed within the bulk of the liquid crystal material (20) i.e. away from the  
30 defects (31,32) within the droplet (30). Indeed, this reduction in the total liquid crystal defect energy within the system is the mechanism by which the defects (33, 34) on the surface of the particle (6) tend to be attracted to the defects (31,32) within the droplet when brought near to each other.

Hence, the total liquid crystal defect energy within the system is minimised when the defect (33,34) on the surface of the particle (6) and the defect within the droplet (31,32) are superposed. In this case, if the geometry of the droplet (30) and the particle (6) allow, then the volume occupied by the defects shall be zero. If the geometry of the droplet (30) and the particle (6) cooperate to a lesser extent then the defects shall occupy a small but finite volume within the droplet. In both of the aforementioned arrangements the total liquid crystal defect energy is minimised and the defects effectively annihilate. This encourages the particle of electrophoretic material (6) to adhere to the internal surface of the droplet (30) and provides a threshold potential for dislodging it and forming a new pair of separate defects.

The operation of the display is illustrated in Figures 6a to 6d.

Referring specifically to Figure 6a, in the absence of an applied electric potential, the system adopts a stable state and the particle of electrophoretic material (6) remains at one end, say the top of the droplet (30). When viewed from above, the particle of electrophoretic material (6) obscures the underlying suspension medium (7) and hence the droplet appears to be substantially the colour of the particle of electrophoretic material (6).

20

Referring specifically to Figure 6b, application of an electric potential (40) of sufficient magnitude with the correct polarity dislodges the particle of electrophoretic material (6) from the top of the droplet, simultaneously creating two defects, one defect (31) at the position where the particle originated and a second defect (33) on the surface of the particle of electrophoretic material (6). The particle (6) moves towards the bottom of the droplet (30) under the influence of the applied electric potential (40). Once the particle of electrophoretic material (6) reaches the bottom of the droplet (30) the defect on the surface of the particle (34) and the defect (32) at the bottom of the droplet (30) become superposed. The total liquid crystal defect energy within the system is now lower than when the electrophoretic particle (6) is disposed within the bulk of the liquid crystal material (20) i.e. away from the defects (31,32) within the droplet (30). The superposed defects effectively annihilate. The particle (6) is retained at the bottom of the droplet (30), even when the electric potential (40) is removed. When viewed from above, the

30

suspension medium (7) obscures the particle of electrophoretic material (6) and hence the droplet appears to be substantially the colour of the suspension medium (7).

5 Referring specifically to Figure 6c, application of a reverse electric potential of low magnitude (41) is insufficient to reform the defect on the surface of the particle (34) and the defect at the bottom of the droplet (32) and therefore the particle of electrophoretic material (6) remains at the bottom of the droplet (30).

10 Referring specifically to Figure 6d, application of a reverse electric potential of larger magnitude (42) dislodges the particle of electrophoretic material (6), simultaneously creating a defect (34) on the surface of the particle (6) and a defect (32) at the bottom of the droplet (30). The particle (6) is returned to its original position at the top of the droplet (30) under the influence of the applied electric potential (42). Once the particle (6) reaches the top of the droplet (30) the two defects (31, 33) superpose. The total  
15 liquid crystal defect energy within the system is once again lower than when the electrophoretic particle (6) is disposed within the bulk of the liquid crystal material (20) i.e. away from the defects (31,32) within the droplet (30). The superposed defects effectively annihilate and the particle (6) is retained in that position.

20 In the embodiments illustrated in Figures 5 and 6, the application of a surface alignment treatment to the particle of electrophoretic material (6) ensures that defects (33, 34) are created in the liquid crystal material on the surface of the particle (6) irrespective of the size of the particle (6). Hence, the particle of electrophoretic material (6) may be arranged to be an optimum size so as to maximise optical scattering and  
25 provide a high contrast display.

In practice, the particle of electrophoretic material (6) is chosen to be sufficiently large so as to provide a high degree of optical scattering when located at the top of the droplet (30). Further, the particle (6) should be sufficiently large so as to hide the  
30 underlying suspension medium when located at the top of the droplet (30); Figures 6a and 6d refer. However, when the particle of electrophoretic material (6) is located at the bottom of the droplet (figures 6b and 6c refer), the suspension medium (7) must be capable of obscuring the electrophoretic particle (6), and this may influence the size of the particle of electrophoretic material (6) chosen for the display.

In general, the radius of the electrophoretic particle (6) may be arranged to be at least 30% of the radius of the droplet (30) in order to provide reasonable hiding of the suspension medium (7). Typically, the electrophoretic particle (6) will exhibit a radius of about 50% of that of the droplet (30). Where the droplet (30) is a spheroid, the radius shall be measured perpendicular to the axis along which the defects (31,32) are arranged. For example, where the droplet (30) is a prolate spheroid and the defects (31,32) are arranged substantially in opposition along the major (long) axis of the prolate droplet (30), then the radius of the droplet (30) shall be measured across the minor (short) axis of the droplet (30).

The dimensions of the particles of electrophoretic material (6) may have an effect on the energy barrier associated with forming the defects in the liquid crystal (20) within a display. Hence, the size of the electrophoretic particles (6) may influence the potential energy barrier and consequently the electric potential threshold within the display. Mindful of the foregoing, the particle size may be selected with a view to tailoring the electric potential threshold within the display.

In practice, the radii of the particles of electrophoretic material (6) may lie within a naturally occurring distribution and this enables a micro-encapsulated display device according to the present invention to display a range of gray levels (gray scale). For example, each pixel in the display may comprise a plurality of droplets (30). From the foregoing, the distribution of the radii of the particles (6) within the droplets (30) will give rise to a corresponding distribution in the electric potential thresholds associated with the droplets (30). Hence, the magnitude of the electric potential applied to each pixel in the display will govern the number of droplets (30) which change optical state within that pixel. In this example, the reflectivity of each pixel is related to the number of droplets within the pixel and the optical state of each pixel. Accordingly, the reflectivity of a pixel will be proportional to the magnitude of the electric potential applied to the pixel (governing the number of droplets which change optical state therein), thereby allowing each pixel to display a range of gray levels.

Although the embodiments of the present invention illustrated in Figures 5 and 6 provide a display with image memory having a non-linear electro-optic transfer characteristic, it may be useful for addressing purposes to incorporate a degree of asymmetry in the electric potential required to move the particles of the electrophoretic

material (6) within the droplets (30), resulting in asymmetric switching thresholds for positive and negative polarity electric potentials. As discussed previously, such asymmetry facilitates multiplexed matrix addressing of multi-cellular displays and allows a technique known as line-ahead blanking to be used to address the display.

5

For clarity, the foregoing descriptions of the embodiments of the present invention have omitted references to particular materials used in the display.

10 Many of the liquid crystal materials and associated dyes used in conventional liquid crystal displays will operate successfully in the embodiments of the present invention described herein. Any of a wide range of oil soluble dyes may also be used.

15 The range of suitable liquid crystal materials includes Nematic liquid crystals, for example Merck® E7, BLO36. The liquid crystal material may be selected according to the performance characteristics required of the display. For example, the switching speed of the display will be related to the viscosity of the suspension medium (7) and hence a low viscosity liquid crystal material may be preferred for applications requiring fast switching speeds.

20 The dyes incorporated in the suspension medium (7) may include any conventional dye suitable for use in a guest-host display system and which is compatible with the liquid crystal material (20) used in the display [see "Dyes in Liquid Crystals", Molecular Crystals & Liquid Crystals, Vol. 150A, A.V. Ivashchenko, V.G. Rumyantsev]. Appropriate dyes include azo dyes and anthraquinone dyes. Oil soluble pharmaceutical  
25 and cosmetic dyes are also be applicable.

Similarly, many of the materials used in conventional electrophoretic displays will operate successfully in the embodiments of the present invention described herein.

30 For example, titanium dioxide,  $\text{TiO}_2$ , is commonly used for the particles of electrophoretic material in conventional electrophoretic displays and may be used as the electrophoretic material (6) in the embodiments of the present invention. One of the reasons why titanium dioxide is commonly used for the particles of electrophoretic material (6) is that it exhibits good optical reflection and scattering properties.  
35 Alternatively, other materials may be used for the particles of electrophoretic material



(6) depending upon the performance specification of the display, for example coloured materials. In particular, the particles of electrophoretic material may comprise spheres having a reflective surface, for example small polymer spheres having a reflective metallic or dielectric surface coating applied thereto. In the case of a dielectric coating, the coating may comprise a reflective multilayer dielectric stack.

As discussed previously, a surface treatment may be applied to the particles of electrophoretic material (6) to encourage a preferred alignment of the liquid crystal material (20) at the surface of the particles (6). Conventional surface treatments known to the skilled person may be applied to the particles of electrophoretic material (6) to achieve specific effects. Typically, the particles of electrophoretic material (6) may have a surface coating of silicon dioxide,  $\text{SiO}_2$ , and an organic coating applied thereto to reduce flocculation and to impart surface alignment properties.

Referring to Figure 7, the particle of electrophoretic material (6) may comprise a composite particle in order to maximise scattering of light and thereby provide good reflectance. In the configuration illustrated in Figure 7, the particle of electrophoretic material (6) comprises scattering particles (45) arranged within a binder (46). The enhanced reflective properties of this arrangement may be attributed to multiple scattering between adjacent and underlying scattering particles (45) within the composite particle. Accordingly, a high proportion of the light incident on the particle (47) is scattered within the composite particle prior to scattering back out of the particle (48).

The scattering particles (45) may comprise any conventional electrophoretic material, for example titanium dioxide,  $\text{TiO}_2$ . Alternatively, the scattering particles (45) may comprise small polymer spheres incorporating a whitener; suitable whiteners include a gas cavity (for example an air pocket), and crushed diamond. The binder (46) is typically any substantially transparent material having a different refractive index to that of the scattering particles (45). The binder (46) may be a cross-linked polymer, for example polymethylmethacrylate (PMMA).

The composite electrophoretic particles (6) referred to above may be fabricated by dispersing particles of titanium dioxide into a monomer system. Monomer droplets are then formed and made spherical, by the action of surface tension, by emulsification in

water having a suitable surfactant mixed therewith. The monomer droplets are subsequently cured. Careful selection of the monomer and surfactant allows control of the liquid crystal anchoring conditions at the surface of the composite electrophoretic particle (6). Typically the surfactant must be thoroughly removed from the particles (6) after curing and prior to any further processing. The final composite electrophoretic particles (6) may be inherently hydrophobic or may be subsequently processed to provide a hydrophobic surface, which is beneficial for subsequent incorporation of the composite particles (6) into the electrophoretic displays described herein.

Alternative to removing the surfactant from the composite electrophoretic particles (6), if a polymer surfactant incorporating hydroxyl functional groups (OH), such as polyvinylalcohol (PVA), is used then the residual layer of polymer that typically cannot be washed from the particle surface may be used as a basis for further coating of the composite electrophoretic particles (6). The OH functional groups can be used to attach any number of different silane compounds to the surface of the polymer particles. By suitable choice of the silane the processability of the particles and the liquid crystal anchoring condition on the particle surface can be adjusted.

The dimensions the particles of electrophoretic material (6) will be related to the materials used in the fabrication of the display and the performance specification of the display. Ideally, the particles of electrophoretic material (6) should be approximately the same size as the wavelength of the light incident on the display in order to achieve maximum optical scattering. Similarly, in the case of composite electrophoretic particles, the scattering particles (45) should be approximately the same size as the wavelength of the light incident on the display in order to achieve maximum optical scattering. In addition, the scattering particles (45) should be well dispersed within each composite electrophoretic particle and there should be a large difference between the refractive index of the scattering particles (45) and the refractive index of the binder (46).

In practice the size of the particles of electrophoretic material (6), or in the case of composite electrophoretic particles the size of the scattering particles (45), is not critical to the optical performance of the device as long as sufficient back-scattering is ensured.

Similarly, the dimensions of the droplets (30) within a micro-encapsulated electrophoretic display systems of the present invention will also be related to the materials used in the fabrication of the display and the performance specification of the display.

5

For the micro-encapsulated electrophoretic display systems of the present invention illustrated in Figures 5 and 6, droplets (30) may be 1-30 $\mu$ m in length, and will typically exhibit a length in the range 5-20 $\mu$ m. For specific applications, the droplets (30) may be selected to have a length in the range 10-15 $\mu$ m. Where the droplet (30) is a spheroid, 10 the droplet length shall be measured parallel to the axis along which the defects (31,32) are arranged. For example, where the droplet (30) is a prolate spheroid and the defects (31,32) are arranged substantially in opposition along the major (long) axis of the prolate droplet (30), then the length of the droplet (30) shall be measured along the major (long) axis of the droplet (30).

15

Similarly, the particles of electrophoretic material (6) suspended within the droplets (30) may have diameters in the range 0.2 to 0.8 times the droplet diameter. Typically, the diameter of the particles of electrophoretic material (6) will be 0.3 to 0.7 times the droplet diameter. For specific applications, the electrophoretic particles (6) will have a 20 diameter in the range 0.4 to 0.6 times that of the droplets (30). Where the droplet (30) is a spheroid, the diameter of the droplet (30) shall be measured perpendicular to the axis along which the defects (31,32) are arranged. For example, where the droplet (30) is a prolate spheroid and the defects (31,32) are arranged substantially in opposition along the major (long) axis of the prolate droplet (30), then the diameter of the droplet 25 (30) shall be taken to be the diameter of the minor (short) axis of the droplet (30).

The embodiments of the display according to the present invention may comprise a suspension medium (7) and particles of electrophoretic material (6) sandwiched between transparent insulating substrates (3a,3b) as is conventional in the prior art 30 (see Figure 1). The substrates may be rigid or may be flexible, for example polymer film. In the case of a micro-encapsulated electrophoretic system (figures 5 and 6 refer), the encapsulant (35) may provide the mechanical support for the suspension medium and the particles of electrophoretic material (6) suspended therein. In this instance one or both of the substrates (3a,3b) may be omitted.

35

For example, in a micro-encapsulated electrophoretic display according to the present invention, the encapsulant (35) may be arranged to provide substantially all of the mechanical support for the droplets (30) containing the liquid crystal material (20) and the particles of electrophoretic material (6).

5

In the embodiments of the present invention described herein, the particles of electrophoretic material (6) are encouraged to migrate within the display by means of an applied electric potential. The means for applying the electric potential may be conventional electrodes (4a,4b) including at least one substantially transparent  
10 electrode located on one surface of the device in order that the display may be viewed. Accordingly, conventional indium tin oxide (ITO) electrodes may be used in the embodiments of the present invention.

Alternatively, conducting polymer electrodes may be used to apply the electric potential  
15 to the device. Conducting polymer electrodes are more robust than ITO electrodes and may be preferred in applications where the display is likely to be subject to mechanical bending forces or where a flexible display is envisaged.

In a further embodiment of the present invention, the electric potential may be applied  
20 to the display via electrodes external to the device. The electric field strength required to operate the device should typically fall within the range 1-10 Volts per  $\mu\text{m}$ . Further, the electric potential may comprise an electrostatic field applied externally to the device via removable electrodes. In this particular configuration the display may operate as a display device for recording a substantially permanent image.

25

With regard to the embodiments of the present invention illustrated in Figures 5 and 6, a micro-encapsulated electrophoretic display may be fabricated using the following processes.

30 The first step in the fabrication of the micro-encapsulated electrophoretic display is to prepare the particles of electrophoretic material (6) for incorporation into the droplets (30). The micro-encapsulated electrophoretic display may incorporate composite electrophoretic particles (6) as described previously (figure 7 refers) and such particles may be prepared as follows.

35

Referring to Figure 8a, a suitable grade of titanium dioxide ( $\text{TiO}_2$ ) is chosen (50) with particle size to give good light scattering properties and preferably with a silica coated surface. The titanium dioxide is processed, to impart hydrophobic properties to the particles (6). For example, a conventional silanation process may be used. This is achieved by dispersing (51) 20g of the titanium dioxide in 400ml of anhydrous cyclohexane and then adding (52) an alkyltrichlorosilane (in this case 0.2g of octyltrichlorosilane) to the dispersion. This is emulsified (53) for 4 hours to ensure complete dispersion of the titanium dioxide in the system and complete reaction of the octyltrichlorosilane with the titanium dioxide surface. The titanium dioxide particles are separated (54) from the cyclohexane in a centrifuge and then mixed (55) with fresh cyclohexane. This process is repeated twice (56) and the titanium dioxide dried (57) in an oven at  $80^\circ\text{C}$  for an hour. The titanium dioxide particles are now hydrophobic (58).

The next step in the fabrication of the composite electrophoretic particles (6) is to disperse (60) the light scattering particles (45), titanium dioxide in this case, in a non-water soluble monomer in the presence of a cross-linking agent and an initiator (e.g. a thermal initiator or a photo-initiator). The mixture is emulsified (61) with an aqueous solution of a suitable surfactant to produce monomer droplets having scattering particles dispersed therein. The initiator is activated (62) to promote cross linking of the monomer. Activation may be by heating in the case of a thermal initiator or illumination with electromagnetic radiation in the case of a photo-initiator.

Referring to Figure 8b, the 20g of titanium dioxide, which is now hydrophobic, is dispersed (60) into a mixture of 49g of methylmethacrylate, 29g of neopentyl glycol dimethacrylate and 2g of thermal initiator lauryl peroxide. This mixture is emulsified (61) into a 1% solution of polyvinylalcohol, with a molecular weight of 125,000. The vigour of this emulsification step and/or the quantity of the polyvinylalcohol additive can be used to control the particle size. This emulsion is then placed (62) in a preheated oven at  $80^\circ\text{C}$  for 1.5 hours. On removal from the oven the product is centrifuged (63), excess water removed and then the particles are remixed (64) with fresh water. This process is repeated several times.

The composite electrophoretic particles (6) may be further treated to facilitate subsequent processing and to control the alignment the liquid crystal on the particles. The following process (65) allows the addition of a silane to the surface on the

composite electrophoretic particles, such as phenyltrichlorosilane, to allow control of the subsequent processing and also of the liquid crystal alignment on the particles. The composite electrophoretic particles are separated from the water and the water is replaced with dry tetrahydrofuran (THF), the rinsing and separation is repeated several  
5 times with the THF. The THF is then replaced with dry cyclohexane and rinsing and separation repeated several times. The composite particles (6) are then in a relatively water free environment so the separated particles can then be added to a mixture of the silane in cyclohexane. The composite particles are left in this mixture for about a hour while mixing. The composite particles are then separated from the cyclohexane  
10 and silane mixture and rinsed in dry cyclohexane several times as before to remove residual silane. The silane reaction with OH groups may not be complete at this stage since some water is required for the reaction, so completion of the reaction is ensured by mixing the separated particles in THF and water. Finally the composite electrophoretic particles are dried (67) in a warm oven to yield a free flowing powder.

15 The next stage involves the dispersion of the electrophoretic particles (6) into liquid crystal droplets (30) and then encapsulation of the droplets (30) to form a dry free flowing powder comprising individually encapsulated droplets (30). Conventional  $\text{TiO}_2$  electrophoretic particles (6) or composite electrophoretic particles (6) may be used.

20 Referring to Figure 9, a traditional encapsulation technique involves the use of gelatine and gum arabic and involves the vigorous emulsification of liquid crystal into a gelatine solution. Hydrophobic electrophoretic particles (6) are mixed with liquid crystal (20) and the mixture is emulsified (72) in an aqueous gelatine solution. The system is further  
25 mixed (73) with gum arabic solution and the encapsulation process continued by slow dilution (76) with water. This causes a layer of coacervate (a colloidal aggregation) to be deposited around the droplets (30). At this stage a gluteraldehyde solution is added (78) to the system to cross link the protein chains and the system is cooled (79) to gel the gelatine while the cross linking process proceeds. These cured capsules (85)  
30 containing liquid crystal (20) and electrophoretic particles (6) are then spray dried (80) to produce a dry free flowing powder.

The encapsulation technique may be modified by the inclusion of an alternative coacervation step. Referring to Figure 10, the liquid crystal (20) and the electrophoretic  
35 particles (6) are emulsified (72) in an aqueous gelatine solution. The system is further

mixed (73) with gum arabic solution. In this embodiment of the present invention the encapsulation process is continued by increasing the pH of the emulsion (75), diluting with water (76) and reducing the pH of the emulsion (77). This causes a layer of coacervate (a colloidal aggregation) to be deposited around the droplets (30). At this stage a gluteraldehyde solution is added (78) to the system to cross link the protein chains and the system is cooled (79) to gel the gelatine while the cross linking process proceeds. These cured capsules (85) containing liquid crystal (20) and electrophoretic particles (6) are then spray dried (80) to produce a dry free flowing powder.

10 The technique for encapsulation is based on traditional gelatine and gum arabic encapsulation processes. Specifically, 1g of a high bloom strength gelatine (isoelectric point pH 8) is dissolved in 25ml of water at 50°C. At the same time 1g of gum arabic is dissolved in 50ml of water at 50°C and put to one side. At the same time 10g of the dried particles of titanium dioxide dispersed in the polymethylmethacrylate, as

15 produced previously (figure 8 refers), is dispersed thoroughly into 20g of a selected commercially available liquid crystal such as E7 (Merck®), into which has been dissolved 2% by weight of an oil soluble (non water soluble) dichroic dye or dyes such as 1-hydroxy-4-[(4-methylphenyl)amino]-9,10-anthracenedione. This mixture of particles (6) and liquid crystal (20) is added slowly into 25ml of aqueous gelatine

20 solution and mixing is continued. To the resulting emulsion sodium hydroxide solution is added to raise the pH to 12. Then the gum arabic solution is mixed with the emulsion. The emulsion is then transferred to a larger beaker and, as in all previous steps, is held at 50°C at the same time mixing is continued slowly. 200ml of water at 50°C is then added to the system and stirred until mixed thoroughly. At this point a 10%

25 solution of acetic acid is then drop by drop to the emulsion until a pH of 4.7 is reached, this triggers coacervation and formation of a protein layer around the droplets (30). To the emulsion is added 0.35g of a 50% gluteraldehyde solution to cross link the capsule walls and the temperature is then reduced to 10°C over half an hour. The pH of the emulsion is then increased to 11. The emulsion is then left to mix for at least 12 hours

30 and the temperature of the system then raised to room temperature. The resulting hardened capsules (85) are dried using standard techniques yielding a free flowing powder.

The foregoing technique describes a gelatine and gum arabic encapsulation technique for the droplets (30) of liquid crystal material (20). A selection of suitable encapsulation techniques are further described in the documents cited in Table 1.0.

Reference	Description
Patent No. US2800457	Green BK and Schleicher L; July 1957; Adapted for use in the embodiments described herein.
Patent No. US3041288	Anthony WH; June 1962; High molecular weight fractionated gelatine-gum arabic coacervation by pH adjustment, can give stronger capsules with less capsule loss by clumping together.
ISBN 0815504497	"Capsule Technology and Microencapsulation 1972" M Gutcho, Noyes Data Corporation, New Jersey, USA, 1972, ISBN 0815504497

5

Table 1.0

However, any suitable encapsulation technique may be employed to fabricate the micro-encapsulated electrophoretic display of the present invention

10

The final step in the fabrication of the micro-encapsulated electrophoretic display is to incorporate the hardened capsules (85) into a bulk encapsulant (35) to form a display device.

15 Referring to Figure 11, the powder of hardened capsules (85) is dispersed (90) into a bulk encapsulant (35) which exhibits a low shrinkage on curing. The encapsulant (35) may comprise a low viscosity and Ultraviolet (UV) or thermally curable binder giving a high density of capsules (85). Note, at this stage the capsules (85) may be spheres or may be spheroids, for example prolate spheroids.

20

This dispersion is then placed (91) between two substrates which incorporate an electrode pattern. An electric or magnetic field is applied (92) to the system to align the capsules (85) appropriately. For example, where the capsules (85) are prolate spheroids and the liquid crystal (20) inside the capsules (85) is aligned with the long axis of the prolate capsules (85), then the capsules (85) shall be aligned with the long axis perpendicular to the substrates. The bulk encapsulant (35) is cured (93), thereby fixing the aligned capsules in the encapsulant (35).

25



Specifically, the dispersion is coated onto a substrate upon which is an electrode, such as indium tin oxide on glass. This electrode may be patterned and also may be metal to give a conductive and reflective surface. The coated layer is typically one to two capsules (85) deep where a capsule (85) is typically about 10 $\mu$ m. Onto this layer is laminated another substrate upon which is a transparent electrode, which may also be patterned such that with the other electrode pattern a matrix array of pixels is generated. The orientations of the capsules (85) are then aligned by the application of an electric field between the substrates. Alternatively, this may be done by a magnetic field. After alignment the encapsulant (35) is cured (93) by exposure to UV radiation.

Alternatively, the steps of aligning (92) the capsules (85) and curing (93) the bulk encapsulant (35) may be transposed. In this embodiment, a thermal curing low shrinkage elastic encapsulant (35) may be used, for example a silicone elastomer system, e.g. Dow Corning® Sylgard® 182. In this case a high expansion coefficient substrate is used. The contraction of the substrate after curing leads to a compression of the encapsulant (35) in the plane of the substrate. This forces the capsules (85) in the encapsulant (35) into a prolate spheroid shape with the long axis perpendicular to the substrate. In turn the liquid crystal (20) inside the capsules, which is in the so called 'boojum' configuration due to nominally planar surface anchoring conditions, aligns with the long axis of the prolate capsules (85). In this embodiment of the present invention the thermal expansion coefficient of the substrate must be chosen to be greater than the thermal expansion coefficient of the encapsulant (35). In use, the encapsulant (35) must remain under compression in the plane of the substrate to ensure that the capsules (85) remain in a prolate spheroid shape.

Another way of achieving the above effect is to use a resilient substrate which can be stretched prior to curing the encapsulant (35). In this embodiment of the present invention, the substrate is stretched prior to curing the encapsulant (35). The substrate is then allowed to contract after the encapsulant (35) has been cured. As before, the contraction of the substrate after curing leads to a compression of the encapsulant (35) in the plane of the substrate. This forces the capsules (85) in the encapsulant (35) into a prolate spheroid shape with the long axis perpendicular to the substrate. As before, a silicone elastomer system, e.g. Dow Corning® Sylgard® 182 may be used in this embodiment of the invention. Again, the encapsulant (35) must remain under

compression in the plane of the substrate to ensure that the capsules (85) remain in a prolate spheroid shape.

5 A further technique for configuring the capsules (85) is to modify the properties of the dispersion after the bulk encapsulant has been cured. In this embodiment of the present invention, the dispersion is coated onto a substrate and the bulk encapsulant (35) is cured, thereby immobilising the capsules (85) and bonding with the substrate. Note, at this stage the capsules (85) may be spheres or may be randomly oriented spheroids. It is possible that, during curing, the bulk encapsulant will shrink and this  
10 may force the capsules (85) in the encapsulant (35) into a prolate spheroid shape with the long axis parallel to the substrate. However, this non-preferred configuration of the capsules is immaterial at this intermediate processing stage. After curing, a suitable material is introduced into the bulk encapsulant (35), for example by diffusion, to expand the encapsulant (35). Since, during curing, the encapsulant (35) has bonded to  
15 the substrate, the encapsulant (35) can only expand in a direction substantially perpendicular to the plane of the substrate. Accordingly, the expansion of the encapsulant (35) forces the capsules (85) into a prolate spheroid shape with the long axis perpendicular to the substrate.

20 As before, a thermal curing low shrinkage elastic encapsulant (35) may be used, for example a silicone elastomer system, e.g. Dow Corning® Sylgard® 182. In the case of a silicone elastomer, a silicone oil may be diffused into the elastomer to cause the elastomer to expand. In practice, the step of diffusing the silicone oil into the cured silicone elastomer comprises soaking the elastomer in the silicone oil. A low molar  
25 mass silicone oil may be used to ensure good diffusion within the cured silicone elastomer.

Referring to Figure 12, there is shown a cross sectional schematic representation of a portion of a micro-encapsulated electrophoretic display (100) according to one aspect  
30 of the present invention. The micro-encapsulated electrophoretic display (100) comprises a plurality of liquid crystal droplets (30), each droplet having an electrophoretic particle disposed therein. The droplets (30) are encapsulated between two substantially parallel substrates (101a, 101b) using an encapsulant (35). In the particular configuration shown in Figure 12, the droplets (30) exhibit a prolate spheroid  
35 configuration with the long axes of the droplets (30) arranged substantially orthogonal

to the substrates (100a,100b). The micro-encapsulated electrophoretic display (100) also comprises a plurality of strip like electrodes (102,103) arranged on the internal surfaces of the substrates (101a,101b). In use, the electrodes are used to apply electric fields to the droplets (30) within the display (100).

5

In the embodiment of the present invention shown in Figure 12, the electrodes (102, 103) are arranged in rows and columns within the display (100). Specifically, the electrodes (102) adjacent the first substrate (101a) are arranged in rows and the electrodes (103) adjacent the second substrate are arranged in columns. Typically, the  
10 row electrodes (102) and the column electrodes (103) are arranged to be substantially perpendicular to each other.

This arrangement of the electrodes in rows and columns provides a matrix of addressable picture elements (pixels) within the display (100). Each pixel is formed by  
15 the intersection of a row electrode (102) and a column electrode (103). Each pixel comprises at least one liquid crystal droplet (30) having an electrophoretic particle (6) disposed therein. The electrophoretic particle (6) within the droplet (30) is controllable by an electric potential applied between the corresponding row and column electrodes for that pixel. Accordingly, matrix addressing of the pixels within the display (100) is  
20 facilitated. In practice, each pixel may comprise a plurality of such droplets (30), thereby enabling each pixel to display a range of gray levels (gray scale). At least one of the electrodes (102,103) may be transparent in order that the underlying droplet (30) / electrophoretic particle (6) is visible.

25 It should be noted that the liquid crystal droplets (30) shown in figure 12 may comprise capsules (85) dispersed in an encapsulant (35). Moreover, the micro-encapsulated electrophoretic display (100) may be configured such that the layer between the substrates (101a,101b) is typically one or two capsules (85) deep (a single capsule depth is shown in figure 12 for clarity).

30

Notwithstanding the inclusion of electrodes in the aforementioned device, the micro-encapsulated electrophoretic display described above may be operated using an electric potential applied to the display via electrodes external to the device. Further, the electric potential may comprise an electrostatic field applied externally to the device  
35 via removable electrodes.

For clarity, it should be noted that in Figure 12 the electrophoretic cells addressed by the first electrode (103) (those on the left hand side of the display (100)) are shown fully switched whereas the adjacent electrophoretic cells addressed by the second electrode (103) are shown partially switched. In this manner in a range of grey levels are obtainable in the display (100).

With regard to the types of dyes used in the embodiments of the present invention, generally all dyes which are soluble in liquid crystal but not water soluble are useful in the embodiments of the present invention described herein. Further, any suitable combination of dyes may be used to create required colours in the device, for example black.

A selection of dyes suitable for use in the embodiments of the present invention described herein is identified in Table 2.0.

CI Name	FDA Name	Chemical Name
Solvent Violet 13	D&C Violet 2	1-hydroxy-4-[(4-methylphenyl)amino]-9,10-anthracenedione
Solvent Yellow 33	D&C Red 17	2-(2-quinolyl)-1,3-indandione
Solvent Green 3	D&C Green 6 K7016	1,4-bis[(4-methylphenyl)amino]-9,10-anthracenedione
Solvent Red 23	D&C Yellow 11 K7064	1-[[4-(phenylazo)phenyl]azo]-2 naphthalenol

Table 2.0

The foregoing embodiments of the phoretic display device according to the present invention have been described predominantly in terms of electrophoretic behaviour. However, as highlighted earlier, magnetophoretic behaviour is equally applicable to the embodiments described herein. Indeed magnetophoretic operation may be employed as a substitute for electrophoretic operation in the previous embodiments. Alternatively, magnetophoretic operation and electrophoretic operation may be used in combination to alter the display state of the devices described herein.

In order to incorporate magnetophoretic behaviour into any of the aforementioned embodiments merely requires use of a phoretic particle having magnetic or ferromagnetic properties. The phoretic particle would then respond to an applied magnetic field in a manner analogous to that described previously for an electric field. For example, in a magnetophoretic display according to the present invention, the display state is switchable by applying a magnetic field of a given field strength to the display. The magnetic field may be provided by a permanent magnet (e.g. in the form of a pen or stylus tipped with a magnet) or could be generated electromagnetically. As before, the phoretic particle would migrate within the device under the influence of the applied field (albeit a magnetic field rather than an electric or electrostatic field as before).

The thresholding effects described previously, arising from the disclinations within the liquid crystal material (20), would operate in a magnetophoretic cell in a manner similar to that described earlier for electrophoretic cells. Accordingly, the advantages discussed herein arising from said thresholding effects would be conferred on a magnetophoretic display in the same way as for an electrophoretic display.

A hybrid display device exhibiting both electrophoretic and magnetophoretic behaviour offers further switching combinations. For example, such a hybrid display could be switched spatially using a localised magnetic field from a pen or stylus tipped with a magnet. However, the display could then be erased by application of an electric potential to the entire display, which would switch the phoretic particles to one state as in a purely electrophoretic display. Moreover, information written on such a display may be recorded by detecting the small current pulse induced by the device switching between display states. This detection may be implemented by incorporating patterned electrodes in the display and erasing the image one line at a time.

Claims

1. A phoretic cell comprising a liquid crystal cell having a liquid crystal material and a phoretic particle therein, the phoretic particle being moveable from a first preferred position at a first side of the liquid crystal cell to a second side of the liquid crystal cell on application of a field,

the liquid crystal cell being adapted such that, when the phoretic particle is not located at the first preferred position, there is a defect associated with the first preferred position and the liquid crystal defect energy of said defect is lower when the phoretic particle is located substantially at the first preferred position within the liquid crystal cell than when the phoretic particle is not so located,

such that the applied field must exceed a threshold level to move the phoretic particle from the first preferred position to the second side of the liquid crystal cell.

2. A phoretic cell according to claim 1 wherein the phoretic particle is moveable reversibly from a second preferred position at the second side of the liquid crystal cell to the first preferred position at the first side of the liquid crystal cell on application of a field,

the liquid crystal cell being adapted such that, when the phoretic particle is not located at the second preferred position, there is a defect associated with the second preferred position and the liquid crystal defect energy of said defect is lower when the phoretic particle is located substantially at the second preferred position within the liquid crystal cell than when the phoretic particle is not so located,

such that the applied field must exceed a threshold level to move the phoretic particle from the second preferred position to the first preferred position within the liquid crystal cell.

3. A phoretic cell according to claim 2 wherein the magnitude of the threshold level associated with moving the phoretic particle from the first preferred position to the second preferred position within the liquid crystal cell is different to that for moving the

phoretic particle from the second preferred position to the first preferred position within the liquid crystal cell.

4. A phoretic cell according to any of claims 1-3 having a plurality of first preferred positions at the first side of the liquid crystal cell, each first preferred position having a defect associated therewith, and a plurality of phoretic particles dispersed within the liquid crystal material.
5. A phoretic cell according to claim 4 when dependent on claim 2 having a plurality of second preferred positions at the second side of the liquid crystal cell, each second preferred position having a defect associated therewith.
6. A phoretic cell according to claim 4 or 5 wherein at least one internal surface of the liquid crystal cell is profiled so as to induce said defects.
7. A phoretic cell according to claim 6 wherein the profile comprises an array of indentations each having a depth,  $d$ , the indentations being arranged at a pitch,  $p$ , within the array.
8. A phoretic cell according to claim 7 wherein the indentations comprise substantially hemispherical indentations.
9. A phoretic cell according to claim 7 or 8 wherein the ratio of the depth of the indentations,  $d$ , to the pitch of the indentations,  $p$ , is at least a quarter.
10. A phoretic cell according to claim 2 or claim 3 when dependent on claim 2 wherein the liquid crystal cell comprises a liquid crystal droplet.
11. A phoretic cell according to claim 10 wherein the phoretic cell comprises a plurality of liquid crystal cells.
12. A phoretic cell according to claim 11 wherein the liquid crystal droplets are substantially spherical, each liquid crystal droplet having a length,  $L$ , equal to the droplet diameter  $D$ .

13. A phoretic cell according to claim 11 wherein the liquid crystal droplets are substantially prolate spheroids, each liquid crystal droplet having a length, L, measured along the major axis and a diameter, D, measured along the minor axis of the liquid crystal droplet, and the first and second preferred positions are arranged substantially in opposition along the major axis of each liquid crystal droplet.
14. A phoretic cell according to claim 12 or 13 wherein the length, L, of the liquid crystal droplet is in the range 1-30  $\mu\text{m}$ .
15. A phoretic cell according to claim 14 wherein the length, L, of the liquid crystal droplet is in the range 5-20  $\mu\text{m}$ .
16. A phoretic cell according to claim 15 wherein the length, L, of the liquid crystal droplet is in the range 10-15  $\mu\text{m}$ .
17. A phoretic cell according to any of claims 12-16 wherein the diameter of the phoretic particle is in the range 0.2 to 0.8 times that of the liquid crystal droplet.
18. A phoretic cell according to claim 17 wherein the diameter of the phoretic particle is in the range 0.3 to 0.7 times that of the liquid crystal droplet.
19. A phoretic cell according to claim 18 wherein the diameter of the phoretic particle is in the range 0.4 to 0.6 times that of the liquid crystal droplet.
20. A phoretic cell according to any of the preceding claims wherein the or each liquid crystal cell further includes an oil soluble dye.
21. A phoretic cell according to claim 20 wherein the dye comprises at least one of a dichroic dye, an azo dye, an anthraquinone dye, a pharmaceutical dye, a cosmetic dye, 1-hydroxy-4-[(4-methylphenyl)amino]-9,10-anthracenedione, 2-(2-quinolyl)-1,3-indandione, 1,4-bis[(4-methylphenyl)amino]-9,10-anthracenedione, and 1-[[4-(phenylazo)phenyl]azo]-2 naphthalenol.
22. A phoretic cell according to any of the preceding claims wherein the or each phoretic particle is adapted to reflect electromagnetic radiation incident thereon.



23. A phoretic cell according to claim 22 wherein the or each phoretic particle comprises titanium dioxide (TiO<sub>2</sub>).

5 24. A phoretic cell according to claim 22 wherein the or each phoretic particle has a reflective coating comprising at least one of a metallic coating and a dielectric coating.

25. A phoretic cell according to any of claims 1-21 wherein the or each phoretic particle comprises a composite particle having a plurality of scattering particles adapted to  
10 scatter electromagnetic radiation incident thereon dispersed within a carrier.

26. A phoretic cell according to claim 25 wherein the carrier comprises a polymer.

27. A phoretic cell according to claim 26 wherein the carrier comprises  
15 polymethylmethacrylate (PMMA).

28. A phoretic cell according to any of claims 25-27 wherein the scattering particles comprise titanium dioxide (TiO<sub>2</sub>).

20 29. A phoretic cell according to any of claims 25-27 wherein the scattering particles comprise polymer spheres, each polymer sphere incorporating at least one of a gas cavity and crushed diamond.

30. A phoretic cell according to any of the preceding claims wherein the liquid crystal  
25 material is a Nematic liquid crystal material.

31. A phoretic cell according to claim 30 wherein the liquid crystal material is Merck® E7.

30 32. A phoretic cell according to any of the preceding claims wherein the applied field is at least one of an electric field and a magnetic field.

33. A phoretic cell substantially as herein before described with reference to figures 3-6 of the accompanying drawings.  
35

34. A display having a first display surface for displaying an image, comprising a phoretic cell as claimed in any of the preceding claims,

5 wherein the phoretic cell is arranged within the display such that the or each first preferred position within the liquid crystal cell is located substantially at the first display surface,

the display being operable by the application of a field across the display.

10 35. A display according to claim 34 having a second display surface disposed remotely to the first display surface, comprising a phoretic cell as claimed in claim 2 or any of claims 3-32 when dependent on claim 2,

15 wherein the phoretic cell is arranged within the display such that the or each second preferred position within the liquid crystal cell is located substantially at the second display surface, and

20 the first and second preferred positions are such that the or each phoretic particle is visible at a display surface when located at one preferred position and is not visible at said display surface when located at the other preferred position.

25 36. A display according to claim 35 comprising a phoretic cell as claimed in claim 11 or any of claims 12-32 when dependent on claim 11, wherein the liquid crystal droplets are disposed within an encapsulant.

37. A display according to claim 36 wherein the encapsulant comprises at least one of a thermally curable polymer, a polymer curable by electromagnetic radiation and a silicone elastomer.

30 38. A display according to claim 36 or 37 wherein the encapsulant comprises Dow Corning® Sylgard® 182.

39. A display according to any of claims 36-38 comprising a phoretic cell as claimed in claim 13 or any of claims 14-32 when dependent on claim 13, wherein the liquid crystal

droplets are arranged such that the major axis of the droplets is substantially orthogonal to a plane parallel with the first display surface.

40. A display according to any of claims 34-39 further comprising means for applying at  
5 least one of an electric field and a magnetic field across the display.

41. A display according to claim 40 wherein the means for applying the field comprises an electrode.

10 42. A display according to claim 41 when dependent on any of claims 35-40 comprising a plurality of electrodes arranged in rows adjacent the first display surface and in columns adjacent the second display surface, the intersection of each row and column electrode defining a pixel within the display, so as to enable matrix addressing of the pixels within the display.

15

43. A display according to claim 41 or 42 wherein the or each electrode comprises at least one of a metal, Indium Tin Oxide (ITO), and a conductive polymer.

44. A display substantially as herein before described with reference to figures 3-6 and  
20 12 of the accompanying drawings.

45. A method of fabricating a display as claimed in any of claims 34-43 comprising the steps of

25 (i) dispersing a plurality of liquid crystal cells as described in claim 10 or any of claims 11-32 when dependent on claim 10, into a curable encapsulant,

(ii) aligning the liquid crystal cells into a preferred alignment,

30 (iii) curing the encapsulant to retain the liquid crystal cells therein.

46. A method of fabricating a display according to claim 45 further comprising the step of applying the dispersion of liquid crystal cells and curable encapsulant onto a substrate.

35

47. A method of fabricating a display according to claim 46 wherein the step of aligning the liquid crystal cells into a preferred alignment is performed after the encapsulant has been cured and comprises the step of expanding the cured encapsulant in a direction substantially perpendicular to the substrate, thereby elongating the liquid crystal cells dispersed therein in a direction substantially perpendicular to the substrate.

48. A method of fabricating a display according to claim 47 wherein the step of expanding the cured encapsulant comprises introducing a material into the cured encapsulant so as to cause the cured encapsulant to swell.

10

49. A method of fabricating a display according to claim 46 comprising the intermediate steps of reversibly deforming the substrate in the plane of the substrate prior to curing the encapsulant and subsequently returning the substrate to its undeformed state after curing the encapsulant, so as to perform the step of aligning the liquid crystal cells, such that the cured encapsulant and the liquid crystal cells dispersed therein are compressed in a plane parallel with that of the substrate.

50. A method of fabricating a display according to claim 49 wherein the step of reversibly deforming the substrate comprises at least one of heating and stretching the substrate.

20

Abstract

Phoretic Display Device

- 5 A phoretic display device comprising a plurality of electrophoretic or magnetophoretic cells, each having a phoretic particle (6) dispersed within a suspension medium (7) comprising a liquid crystal material (20). The phoretic cell is adapted to induce defects (21;31,32), sometimes known as disclinations, in the alignment of the liquid crystal material (20) within the cell which act to exert a retentive force on the phoretic particle
- 10 (6) when in the vicinity of the defects (21;31,32). The configuration of the display introduces a threshold level in the electric or magnetic field required to move the phoretic particle (6) between defects (21;31,32) within the cell. Accordingly, the non-linear electro-optic or magneto-optic transfer characteristics of the display facilitates matrix addressing of the cells therein. The display (100) may comprise a plurality of
- 15 prolate spheroid phoretic cells (30) arranged in an encapsulant (35), the major (long) axis of each cell (30) arranged substantially perpendicular to the plane of the display.

[Figure 5 should accompany the abstract]




Figure 1  
Prior Art




Figure 2  
Prior Art




Figure 3




Figure 4




Figure 5






Figure 6




Figure 7




Figure 8a




Figure 8b




Figure 9




Figure 10




Figure 11.




Figure 12



THE PATENT OFFICE  
28 AUG 2003  
Reception Unit  
International Unit

PCT Application  
**GB0303512**



**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☒ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☒ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**